

KAESER
COMPRESSORS

Built for a lifetime.™



Mobilair™ Rotary Screw Compressors

Portable Compressors

Capacities from: 50 to 1200 cfm

Pressures from: 70 to 217 psig

www.kaeser.com

Mobilair™

Portable air compressors

Kaeser Compressors' superior line of Mobilair™ portable air compressors are designed to pack the most efficiency possible into a compact, rugged design. They are exceptionally durable and are built to withstand even the most demanding job sites. Their superior German engineering means reliable performance year after year. Whether you rent or operate them, Mobilairs' long life mean they can spend more time out in the field earning you rent or getting jobs done.

Versatile

Kaeser Mobilair portable compressors are available in a wide range of sizes and pressures and are suited for many applications including, but not limited to, sandblasting, pavement breaking, and general air tool use. Their extensive options allow customization to meet virtually any demand. Units are ideal for rental houses, repair trucks, and municipalities.

Reliable


Each Mobilair features a heavy duty chassis and canopy design to provide excellent protection from corrosion and the elements. Units feature powerful, yet efficient engines from names you can trust: Honda, Kubota, Deutz, and Mercedes Benz. The package air flow design keeps the motor cool, even under demanding conditions. Features like our cold start battery assure year round availability.

Low cost of ownership

Mobilair compressors feature larger, slower turning Sigma Profile™ airends for longer life and better efficiency with 15-20% more air per gallon of fuel than our competition. Superb reliability and simple maintenance save time and money. The patented Anti-frost Valve protects air tools from freezing when the ambient temperature is lower, significantly increasing tool service life.

User-friendly

Mobilair compressors are simple to operate, provide excellent component accessibility, and are easy to maintain. Their enhanced safety features and very low noise levels make them the perfect choice for any job site. Towable models have excellent handling with even weight distribution and feature a torsion bar suspension system. Superior efficiency means you can run them longer before refueling.



M15, M17

Compact powerhouses

The smallest Mobilair compressors are more than capable of powering breakers, drills, saws, grinders, impact wrenches, and even impact borers. The higher pressure version is the ideal choice for fiber optic cable moles. In addition, the compressor can be equipped with an external compressed air aftercooler for certain applications that may require cool and condensate-free compressed air.



COMPRESSOR			GASOLINE ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery at		Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L * x W x H (in.)
	100 psig (cfm)	217 psig (cfm)								
M15	50	—	Honda GX630	14.8	3000	2200	5.3	445	1 x 1/2"	42½ x 31½ x 31
M17	60	35	Honda GX630	17.4	3300	2400	5.3	450	1 x 1/2"	42½ x 31½ x 31

*Length includes tow bar
Sound level maximum is 82 db(A) at 23 feet.

Specifications are subject to change without notice.

M27, M27 Utility



COMPRESSOR			DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery (cfm)	Working Pressure (psig)	Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L* x W x H (in.)
M27	92	100	Kubota D1105-B	21	2850	2100	10.6	1224	2 x 3/4"	119 x 49½ x 51¼
M27 Utility	92		Kubota D1105-B	21	2850	2100	10.6	1267	2 x 3/4"	80 x 39 ³ / ₁₆ x 42 ⁵ / ₁₆

*Length includes tow bar

Sound level maximum is 76 db(A) at 23 feet.

Specifications are subject to change without notice.

M58, M58 Utility




COMPRESSOR			DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery at		Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L * x W x H (in.)
	100 psig (cfm)	145 psig (cfm)								
M58	210	175	Kubota V2403-CR-E4B	48	2600	1800	28	2590	2 x 3/4" / 1 x 1"	145 x 68 x 62
M58 Utility	210	175	Kubota V2403-CR-E4B	48	2600	1800	28	2043	2 x 3/4" / 1 x 1"	84 ⁵ / ₈ x 33 ¹ / ₈ x 55

*Length includes tow bar
 Sound level maximum is 76 db(A) at 23 feet.

Specifications are subject to change without notice.

M114, M125



COMPRESSOR					DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery at				Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L* x W x H (in.)
	100 psig (cfm)	145 psig (cfm)	175 psig (cfm)	205 psig (cfm)								
M114	375	345	295	265	Deutz TCD 3.6L4	103.3	2200	1600	45	4111	3 x 3/4" 1 x 1 1/2"	191 ⁷ / ₁₆ x 73 ⁷ / ₁₆ x 63
M125	405	405	380	342	Deutz TCD 4.1 L04	140	2200	1500	45	4580	3 x 3/4" 1 x 1 1/2"	188 x 74 x 68

*Length includes tow bar
Sound level maximum is 76 db(A) at 23 feet

Specifications are subject to change without notice.

M250, M350



COMPRESSOR					DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery at				Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L * W x H (in.)
	125 psig (cfm)	145 psig (cfm)	175 psig (cfm)	205 psig (cfm)								
M250	900	875	795	705	Mercedes-Benz OM926LA	288	1800	1200	66	7760	3 x 3/4" 1 x 2"	225 x 77¾ x 89¼
M350	1200	1095	965	850	Mercedes-Benz OM501LA	327	1650	1200	172	12,566	2 x 1" 1 x 2½"	251 x 82 ⁷ / ₁₆ x 96

*Length includes tow bar
Sound level maximum is 76 db(A) at 23 feet.

Specifications are subject to change without notice.

Technical Specifications

	M15*	M17*	M27	M27 Utility	M58	M58 Utility	M114	M125	M250	M350
Sigma Profile airtend	S	S	S	S	S	S	S	S	S	S
Lifting eye	S	S	S	S	S	S	S	S	S	S
XL tool box	N/A	N/A	S	S	S	N/A	S	S	S	S
Anti-frost valve	N/A	N/A	S	S	S	S	NA	NA	NA	NA
Cold start battery	S	S	S	S	S	S	S	S	S	S
DOT approved lights & reflectors	N/A	N/A	S	N/A	S	N/A	S	S	S	S
Push to load switch	N/A	N/A	N/A	N/A	S	S	S	S	S	S
Stationary / Skid mount	O	O	O	S	O	S	O	O	O	O
Polyethylene enclosure	S	S	S	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Powder-coated steel enclosure	N/A	N/A	N/A	S	S	S	S	S	S	S
Aftercooler with separator	O	O	O	O	O	O	O	O	O	O
5 year warranty	O	O	O	O	O	O	O	O	O	O
Check valve for sandblasting	N/A	N/A	S	S	S	S	S	S	S	S

S: Standard, O: Optional, N/A: Not available.

*M15 and M17 are available stationary mounted

Specifications are subject to change without notice.

Optional 5 Year Warranty

To protect your investment, all of our Mobilair compressors are available with an optional 5 year warranty on the compressor airtend.



**KAESER
COMPRESSORS**

Built for a lifetime.™



Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Vérendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

**Kaeser Compresores de México
S de RL de CV**
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

**Kaeser Compresores de
Guatemala y Cia. Ltda.**
Calz. Atanasio Tzul 21-00, zona 12
El Cortijo II, Bodega 501
01012—Guatemala City
Telephone: +502 2412-6000
info.guatemala@kaeser.com

Certified Management Systems

