

DISCHARGE HOSE

7801 – BLUE PVC DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	7801-150X50MF*
2" X 50'	7801-2X50MF
2-1/2" X 50'	7801-250X50MF*
3" X 50'	7801-3X50MF
4" X 50'	7801-4X50MF
6" X 50'	7801-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD
3/4" & 1" SIZES AVAILABLE WITH HD BRASS MXF

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	7801-150X50CE
2" X 50'	7801-2X50CE
2-1/2" X 50'	7801-250X50CE
3" X 50'	7801-3X50CE
4" X 50'	7801-4X50CE
6" X 50'	7801-6X50CE

AVAILABLE WITH BALL & SOCKET COUPLINGS

300 FT MAX ROLL LENGTH

BULK HOSE

-5 TO +170 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
3/4"	7801-075	140	0.08
1"	7801-100	110	0.11
1-1/4"	7801-125	80	0.14
1-1/2"	7801-150	80	0.19
2"	7801-200	80	0.24
2-1/2"	7801-250	65	0.30
3"	7801-300	80	0.36
4"	7801-400	70	0.53

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
5"	7801-500	40	0.65
6"	7801-600	60	0.87
8"	7801-800	35	1.30
10"	7801-10	35 / 80*	1.90 / 2.15
12"	7801-12	35 / 60*	2.45 / 2.75
14"	7801-14	30	2.70
16"	7801-16	30	3.10

*10" & 12" ALSO AVAILABLE IN HEAVY GRADE

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE

DISCHARGE HOSE

7801R – RED HD PVC DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	7801R-150X50MF*
2" X 50'	7801R-2X50MF
2-1/2" X 50'	7801R-250X50MF*
3" X 50'	7801R-3X50MF
4" X 50'	7801R-4X50MF
6" X 50'	7801R-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	7801R-150X50CE
2" X 50'	7801R-2X50CE
2-1/2" X 50'	7801R-250X50CE
3" X 50'	7801R-3X50CE
4" X 50'	7801R-4X50CE
6" X 50'	7801R-6X50CE

AVAILABLE WITH BALL & SOCKET COUPLINGS

300 FT MAX ROLL LENGTH

BULK HOSE

-5 TO +170 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT	FULL ROLL LENGHT
1-1/2"	7801R-150	150	0.28	300'
2"	7801R-200	150	0.34	300'
2-1/2"	7801R-250	150	0.40	300'
3"	7801R-300	150	0.55	300'
4"	7801R-400	150	0.85	300'
6"	7801R-600	150	1.34	300'
8"	7801R-800	115	1.90	300'

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE

DISCHARGE HOSE

3200 / 3220 – MILL DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	3200-150X50MF*
2" X 50'	3200-2X50MF
2-1/2" X 50'	3200-250X50MF*
3" X 50'	3200-3X50MF
4" X 50'	3200-4X50MF
6" X 50'	3200-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	3200-150X50CE
2" X 50'	3200-2X50CE
2-1/2" X 50'	3200-250X50CE
3" X 50'	3200-3X50CE
4" X 50'	3200-4X50CE
6" X 50'	3200-6X50CE

DOUBLE JACKET ASSEMBLIES AVAILABLE
TYPE #3220 (SEE CHART BELOW)

SINGLE JACKET

BULK HOSE

100 FT MAX THROUGH 4 INCH

DOUBLE JACKET

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1"	3200-100	150	0.16
1-1/2"	3200-150	150	0.20
2"	3200-200	150	0.27
2-1/2"	3200-250	150	0.37
3"	3200-300	150	0.43
4"	3200-400	150	0.62
6"	3200-600	115	1.10

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	3220-150	300	0.29
2"	3220-200	300	0.40
2-1/2"	3220-250	300	0.50
3"	3220-300	250	0.63
4"	3220-400	250	0.76

NOT RATED FOR FIRE PROTECTION

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
 HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE

DISCHARGE HOSE

FIRE HOSE ASSEMBLIES



SINGLE JACKET ASSEMBLIES **150 PSI SERVICE / 300 PSI TEST** **NST / NH FIRE THREAD**

1-1/2" X 50'	3200-150X50NSTRL
2-1/2" X 50'	3200-250X50NSTRL

AVAILABLE IN 500 PSI TEST #3202



DOUBLE JACKET ASSEMBLIES **200 PSI SERVICE / 400 PSI TEST** **NST / NH FIRE THREAD**

1-1/2" X 50'	3220-150X50NSTRL
2-1/2" X 50'	3220-250X50NSTRL

AVAILABLE IN 800 PSI TEST #3228

DOUBLE JACKET ASSEMBLIES **200 PSI SERVICE / 400 PSI TEST** **NPSH THREAD**

1-1/2" X 50'	3220-150X50MFRL
2-1/2" X 50'	3220-250X50MFRL

AVAILABLE IN 800 PSI TEST #3228

ASSEMBLIES ARE TESTED & STENCILED
PER NFPA STANDARDS

ALUMINUM COUPLINGS STANDARD • BRASS COUPLINGS AVAILABLE BY REQUEST
MUNICIPAL THREAD PATTERNS AVAILABLE BY SPECIAL ORDER, PLEASE INQUIRE

CUSTOM FIRE HOSE OPTIONS

SINGLE JACKET 500 PSI TEST & DOUBLE JACKET 800 PSI TEST
RUBBER LINED & POLYURETHANE LINED

ABRASION RESISTANT COLOR-COATING AVAILABLE IN:



COLOR SHADES MAY VARY, ADDITIONAL LEAD TIME MAY APPLY

UL LISTED AND NSF COMPLIANT HOSE AVAILABLE

COUPLING TYPES INCLUDE:

BRASS PIN LUG
BRASS ROCKER LUG
ALUMINUM ROCKER LUG
SPECIAL THREADS AVAILABLE
STORZ COUPLINGS AVAILABLE



DISCHARGE HOSE

9821 – NITRILE RUBBER DISCHARGE

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



ALSO AVAILABLE
IN BLACK COVER

1-1/2" X 50'	9821-150X50CE
2" X 50'	9821-2X50CE
2-1/2" X 50'	9821-250X50CE
3" X 50'	9821-3X50CE
4" X 50'	9821-4X50CE
6" X 50'	9821-6X50CE

ADDITIONAL CONFIGURATIONS AVAILABLE

AVAILABLE WITH BALL & SOCKET COUPLINGS

ASSEMBLIES WITH ROCKER LUG ANODIZED ALUMINUM M&F COUPLINGS



ANODIZED ALUMINUM
FULL FLOW COUPLINGS

HOSE SIZE (ID)	THREAD TYPE	ITEM NUMBER
1-1/2" X 50'	NPSH	9821-150X50MFRL
1-1/2" X 50'	NST	9821-150X50NSTRL
2" X 50'	NPSH	9821-2X50MFRL
2-1/2" X 50'	NPSH	9821-250X50MFRL
2-1/2" X 50'	NST	9821-250X50NSTRL
3" X 50'	NPSH	9821-3X50MFRL

250 PSI / 500 TEST STANDARD, 300 PSI / 600 TEST AVAILABLE
4", 5", & 6" AVAILABLE IN NST OR STORZ QUICK CONNECT

100 FT MAX ROLL LENGTH

BULK HOSE

-20 TO +210 DEG F

ALSO AVAILABLE
BY CUSTOM ORDER:

ADDITIONAL COLORS
URETHANE VERSION
300 & 660 FT LENGTHS
(MINIMUM MAY APPLY)

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	9821-150	250	0.26
2"	9821-200	250	0.35
2-1/2"	9821-250	250	0.47
3"	9821-300	250	0.65
4"	9821-400	200	0.85
6"	9821-600	150	1.60
8"	9821-800	150	2.30

REUSABLE COUPLINGS
AVAILABLE UP TO 12"



GROOVED OR THREADED
ANODIZED ALUMINUM

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE

DISCHARGE HOSE

9801 – RUBBER DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	9801-150X50MF*
2" X 50'	9801-2X50MF
2-1/2" X 50'	9801-250X50MF*
3" X 50'	9801-3X50MF
4" X 50'	9801-4X50MF
6" X 50'	9801-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	9801-150X50CE
2" X 50'	9801-2X50CE
2-1/2" X 50'	9801-250X50CE
3" X 50'	9801-3X50CE
4" X 50'	9801-4X50CE
6" X 50'	9801-6X50CE

ASSEMBLY NUMBERS SHOWN ARE FOR 2-PLY REINFORCED HOSE
4-PLY REINFORCED HOSE AVAILABLE, # 9801H (SEE CHART BELOW)

AVAILABLE WITH BALL & SOCKET COUPLINGS

100 FT MAX LENGTH TO 10"

BULK HOSE

-25 TO +180 DEG F

SIZE (ID)	ITEM NUMBER	2-PLY PSI RATING	4-PLY PSI RATING	SIZE (ID)	ITEM NUMBER	2-PLY PSI RATING	4-PLY PSI RATING
1-1/2"	9801_-150	150	250	5"	9801_-500	150	200
2"	9801_-200	150	250	6"	9801_-600	100	150
2-1/2"	9801_-250	150	250	8"	9801_-800	100	125
3"	9801_-300	150	225	10"	9801_-10	100	125
4"	9801_-400	150	200	12"	9801_-12	100	125

LARGE DIAMETER HOSE & ABRASION RESISTANT TUBE MATERIALS AVAILABLE

NOT RECOMMENDED FOR SAND, GRAVEL, OR CEMENT DISCHARGE APPLICATIONS

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE