

TPG SERIES PORTABLE GENERATORS

TSURUMI TPG4 Series Generators are designed to withstand the severe conditions of construction jobsites or industrial applications, especially where extra durability and dependable, stable power are required. Ideal to supply the power to Tsurumi's single-phase submersible pumps and all your electrical power tools such as drills, saws, lighting and heaters.

TPG4 Series Generators Features *powered by Honda*

- High capacity fuel tank with fuel gauge for extended run time.
- Large, silent muffler with USDA qualified spark arrestor to greatly reduce noise.

Optional Accessories - See page 29 & 31

- PGWK-200X Wheel Kit
- PGLB-1X Lifting Bail



Powered by **Honda OHV engine** for efficient fuel and oil construction with oil alert system to shut off motor if oil fails below safe operating level.

Large air filter for **superior emission control**.

Automatic idle control reduces fuel consumption, noise, and engine wear.

Auto idle control switch on control panel.
(Not available on TPG4-3000HDX)

Rubber vibration pads isolate generator / engine set for **maximum protection and noise reduction**.



SPECIFICATIONS - TPG4-3000HDX / 4500HDX / 6000HDX / 7000HDX / 7000HDXE



| | TPG4-3000HDX | TPG4-4500HDX |
|------------------------------------|---|--|
| Max. / Rated Output (watts) | 2600 / 2200 | 4500 / 3600 |
| Max. / Rated Current (120V / 240V) | 23.3 / 18.3 | 37.5/30, 18.7/15 |
| Voltage (V) (60Hz) | 120 | 120 / 240 |
| AC Outlet Replacement | 1-NEMA 5-20R Duplex (20A, 12A, W/GFCI) | 2-NEMA 5-20A Duplex (20A, 12A, W/GFCI) 1-NEMA L5-30R (30A, 120V, Twist Lock) 1-NEMA L14-30R (30A, 120/240V, Twist Lock) |
| Engine Model | GX160T2 | GX240T2 |
| Maximum HP | 5.5 (3600RPM) | 8.0 (3600RPM) |
| Displacement | 163 (10inch ³) | 242 (15inch ³) |
| Fuel Tank Capacity (gallon) | 4.2 | 6.6 |
| Running Time (Rated load) | 12.1 | 12.5 |
| Starting System | Recoil | Recoil |
| Noise Level (Rated Load) | 64dB | 68dB |
| Shipping Size (LxWxH) (inches) | 24.4 x 19.5 x 20.5 | 27.6 x 23.4 x 22.6 |
| Shipping Weight (lbs.) | 110 | 161 |

| | TPG4-6000HDX | TPG4-7000HDX TPG4-7000HDXE |
|------------------------------------|--|-------------------------------|
| Max. / Rated Output (watts) | 5500 / 4800 | 6800 / 6000 |
| Max. / Rated Current (120V / 240V) | 45.8/40, 22.9/20 | 56.7/50, 28.3/25 |
| Voltage (V) (60Hz) | 120 / 240 | 120 / 240 |
| AC Outlet Replacement | 2-NEMA 5-20A Duplex (20A, 12A, W/GFCI) 1-NEMA L5-30R (30A, 120V, Twist Lock) 1-NEMA L14-30R (30A, 120/240V, Twist Lock) | |
| Engine Model | GX340T2 | GX390T2 |
| Maximum HP | 11.0 (3600RPM) | 13.0 (3600RPM) |
| Displacement | 337 (21inch ³) | 389 (24inch ³) |
| Fuel Tank Capacity (gallon) | 6.6 | 6.6 |
| Running Time (Rated load) | 8.5 | 7.6 |
| Starting System | Recoil | Recoil (HDX), Electric (HDXE) |
| Noise Level (Rated Load) | 72dB | 78dB |
| Shipping Size (LxWxH) (inches) | 27.6 x 23.4 x 22.6 | 27.6 x 23.4 x 22.6 |
| Shipping Weight (lbs.) | 183 | 192(HDX), 199(HDXE) |

See Page 31 for Generator Accessories