

VIBRATORY PLATES CF / CFR



The vibratory plate compactors of the CF 2 and CF 3 series distinguish themselves by premium operating comfort, compact dimensions and optimum running characteristics. Their fields of application: compaction work in landscaping and repair work.

The special low-vibration guide bar (CF 2 and CF 3) reduces the hand/arm vibrations and ensures comfortable work. In addition, the guide bar features a soft, user-friendly plastic coating.

The CF 1 A Hd and CF 2 A Hd were specially designed for asphalt compaction.

The CFR 90 is an alternative to the "standard" vibratory plates. The almost round base plate allows for high maneuverability in confined areas, for example in cable trenches or along curbs.






Picture with accessories

CFR 90

CF 1 Hd / CF 1 A Hd

TYPE	CFR 90	CF 1 Hd / CF 1 A Hd
Operating weight CECE (lbs)	198.4	139/143.3
Working width (in)	17	13.8
Centrifugal Force (lbs)	3,147.3	2,248
Frequency (Hz)	85	95
Engine	Honda GX160 4-stroke, gasoline	Honda GX120 4-stroke, gasoline
Engine output max (HP)	4.9	3.3
Power output at operating speed (HP)	3.7 at 3,000 rpm	2.5 at 3,000 rpm
Working speed (ft/min)	85.3	85.3
Dimensions (in)	18 x 17 x 38.6	44.5 x 14 x 38





CF 2 Hd



Picture with accessories

CF 2 A Hd



Picture with accessories

CF 3

TYPE	CF 2 Hd	CF 2 A Hd	CF 3 Hd / CF 3 / 60 Hd	CF 3 / CF 3 / 60
Operating weight CECE (lbs)	183	181	207/236	238/269
Working width (in)	17.7	17.7	19.7/23.6	19.7/23.6
Centrifugal Force (lbs)	3,372	3,372	4,496	4,496
Frequency (Hz)	95	95	95	95
Engine	Honda GX160 4-stroke, gasoline	Honda GX160 4-stroke, gasoline	Honda GX160 4-stroke, gasoline	Honda GX120 4-stroke, gasoline
Engine output max (HP)	4.9	4.9	4.9	4.8
Power output at operating speed (HP)	3.7 at 3,000 rpm	3.7 at 3,000 rpm	3.7 at 3,000 rpm	4.2 at 3,000 rpm
Working speed (ft/min)	85	85	85	78.7
Dimensions (in)	44.5 x 17.7 x 37.8	44.5 x 17.7 x 37.8	45.7 x 19.7/23.6 x 37.8	45.7 x 19.7/23.6 x 37.8

→ AVAILABLE ACCESSORIES

- Integrated wheel kit.
- Water sprinkler system (for asphalt compaction).
- Polyurethane pad.



VIBRATORY PLATE CF 2 HD

A powerful light-weight



ADVANTAGES

- Compact machine dimensions.
- Durable and rugged construction.
- High working speed, good operating characteristics.
- Foldable, low-vibration guide bar.
- Work without getting tired thanks to a low hand-arm vibration.
- Remote control throttle, throttle lever on the guide bar.
- Water sprinkler system with 12 liter tank (optional).



AREAS OF APPLICATION

- Landscape.
- Compacting asphalt or pavers for maintenance.