

# RENEGADE

# TLB-25

## TRACTOR LOADER BACKHOE

DESIGNED AND MANUFACTURED BY TAMARACK INDUSTRIES

**BUILT TOUGH FOR THE  
RENTAL INDUSTRY**

**4600 LB BREAK-OUT FORCE**

**1600 LB LIFT CAPACITY**



**8'7" DIG DEPTH**

**1/2 YARD CAPACITY**

### RENEGADE ADVANTAGE

- INDUSTRY FIRST **200 DEGREE** BACKHOE SWING ANGLE
- **CURVED ARM LOADER:** BETTER OPERATOR SIGHT LINES AND STRENGTH
- **60" LOADER BUCKET** WITH REMOVABLE BLACK CAT WEAR EDGE
- **ACCESSORY REMOTE HYDRAULICS** ON LOADER VALVE (FOR LOADER **GRAPPLE**)
- **ACCESSORY REMOTE HYDRAULICS** ON BACKHOE VALVE (FOR BACKHOE **THUMB**)
- ANGLED BACKHOE OUTRIGGERS

[WWW.TAMARACK-INDUSTRIES.COM](http://WWW.TAMARACK-INDUSTRIES.COM)



**Tamarack  
Industries**

# TLB-25 SPECIFICATIONS

<b>ENGINE:</b>	Yanmar 25 HP Tier 4 Final Diesel / Honda iGX800 Gas
<b>LUBRICATION:</b>	Pressurized Filter
<b>DRIVE MOTORS:</b>	2 Heavy Duty Gerotors

## CAPACITIES:

<b>Fuel Tank</b>	US: 5 Gallons	Metric: 19 Liters
<b>Hydraulic Tank</b>	US: 10 Gallons	Metric: 38 Liters

<b>LOADER CAPACITY:</b>	<b>U.S.</b> 1/2 CU. Yard	<b>Metric-</b> 0.254 m <sup>3</sup>
<b>REAR BUCKET ROTATION:</b>	180 Degrees	
<b>REAR BOOM SWING:</b>	200 Degrees	
<b>FRONT BUCKET ROLLBACK:</b>	35 Degrees	
<b>SPEED RANGE:</b>	0 - 6 mph	
<b>OPTIONAL EQUIPMENT:</b>	Quick attach fits all Bobcat attachments	

## HYDRAULIC SYSTEM FOR BACKHOE & ENDLOADER:

<b>Pump</b>	Gear Type
<b>Flow</b>	9 GPM at 3600 RPM
<b>Pressure</b>	3000 PSI
<b>Loader Valve</b>	3 Spool Monoblock
<b>Backhoe Valve</b>	7 Spool Stack Type
<b>Cylinders</b>	2", 2 1/2"

MEASUREMENTS:	U.S.	Metric
<i>Backhoe Digging Depth</i>	104 inches	264 cm
<i>Loader Dump Height</i>	98 inches	249 cm
<i>Backhoe Reach</i>	154 inches	391 cm
<i>Rear Bucket Dump Height</i>	103 inches	262 cm
<i>Front Tire to Front Bucket</i>	53 inches	134 cm
<i>Wheelbase</i>	83 inches	211 cm
<i>Transportation Length</i>	17 feet	518 cm
<i>Transportation Weight</i>	4180 lbs	1896 kg
<i>Transportation Height</i>	84 inches	213 cm
<i>Overall Width</i>	60 inches	152 cm
<i>Overall Height</i>	83 inches	211 cm
<i>Ground clearance</i>	13 inches	33 cm

## FRONT AXLE:

<b>Construction</b>	Heavy Duty Crossbeam
<b>Spindle Size</b>	1 3/4" Diameter
<b>Steering</b>	Hydraulic Power

## REAR AXLE:

<b>Ratio</b>	Hydrostatic
--------------	-------------

## TIRES:

<b>Front</b>	23" x 10.5" x 12" 4 Ply
<b>Rear</b>	31" x 15.5" x 15" High Flotation

## FEATURES

- **COMPACT DESIGN**
- **TWO WHEEL DRIVE**
- **RIGID, ALL STEEL CONSTRUCTION**
- **LOW MAINTENANCE COSTS**
- **UNIVERSAL QUICK ATTACH: FITS ALL BOBCAT ATTACHMENTS**
- **REVERSIBLE SEAT**
- **TRAVELING SPEED 6 MPH**

